
ConfigObject Documentation

Release 1.2

Gael Pasgrimaud

October 25, 2016

Contents

1 Module Contents	3
Python Module Index	5

`ConfigObject` is a wrapper to the python `ConfigParser` to allow to access sections/options with attribute names:

```
>>> from ConfigObject import ConfigObject
>>> config = ConfigObject()

>>> config.section.value = 1
```

Values are stored as string:

```
>>> config.section.value
'1'
```

Values are returned as `ConfigValue` to convert result to other types:

```
>>> config.section.value.as_int()
1
```

Here is how list are stored:

```
>>> config.section.value1 = list(range(2))
>>> print(config.section.value1)
0
1
>>> config.section.value1.as_list()
['0', '1']
```

You can use keys:

```
>>> config['set']['value'] = 1
>>> config['set']['value'].as_int()
1
```

You can set a section as dict:

```
>>> config.dict = dict(value=1, value2=['0', '1'])
>>> config.dict.value.as_int()
1
>>> config.dict.value2.as_list()
['0', '1']
```

Update it:

```
>>> config.dict.update(value2=[1, 2])
>>> config.dict.value2.as_list()
['1', '2']
```

See what your section look like:

```
>>> config['set']
{'value': '1'}
```

Delete options:

```
>>> del config['set'].value
>>> config['set']
{}
```

Playing with files:

```
>>> filename=os.path.join(tempfile.gettempdir(), 'config.ini')
>>> config = ConfigObject(filename=filename)
>>> config.section = dict(value=1)
>>> config.write()

>>> config = ConfigObject(filename=filename)
>>> config.section.value.as_int()
1

>>> os.remove(filename)
```

Module Contents

```
class ConfigObject.ConfigObject(*args, **kwargs)
    ConfigParser wrapper
```

```
class ConfigObject.ConfigValue
```

as_bool (*true=True, false=False*)
convert value to bool:

```
>>> config = ConfigObject()
>>> config.bools = dict(true=True, false=False)
```

```
>>> config.bools.true
'true'
>>> config.bools.true.as_bool()
True
>>> config.bools.true.as_bool('on', 'off')
'on'
```

```
>>> config.bools.false
'false'
>>> config.bools.false.as_bool()
False
>>> config.bools.false.as_bool('on', 'off')
'off'
```

```
>>> config.bools.none.as_bool()
False
```

as_float()
convert value to float

as_int()
convert value to int

as_list (*sep=None*)
convert value to list:: >>> config = ConfigObject() >>> config.listes = dict(liste=[0, 1], string='1;2;3')

```
>>> print(config.listes.liste)
0
1
>>> config.listes.liste.as_list()
['0', '1']
```

```
>>> config.listes.string.as_list(sep='; ')
['1', '2', '3']
```

`ConfigObject.config_module(name, file, *filenames, **defaults)`

Allow to set a `ConfigObject` as module. You have to add this to `yourproject/config.py`:

```
# -*- coding: utf-8 -*-
from ConfigObject import config_module
import os
filename = os.path.join(os.path.dirname(__file__), 'config.ini')
config = config_module(__name__, __file__, filename)
```

Then you are able to use `from yourproject import config` where `config` is the `ConfigObject` itself.

C

[ConfigObject](#), 3

A

`as_bool()` (`ConfigObject.ConfigValue` method), 3
`as_float()` (`ConfigObject.ConfigValue` method), 3
`as_int()` (`ConfigObject.ConfigValue` method), 3
`as_list()` (`ConfigObject.ConfigValue` method), 3

C

`config_module()` (in module `ConfigObject`), 4
`ConfigObject` (class in `ConfigObject`), 3
`ConfigObject` (module), 1
`ConfigValue` (class in `ConfigObject`), 3